

OMNI MINI KIOSK TERMINAL

Combine Design, Power and Quality to Meet the POS Demands of Today

In today's ever-changing POS environment, businesses are demanding more from their POS suppliers. From a quality product, top-notch customer service, to simple self-troubleshoot instructions, the need for superior POS capabilities is higher than ever. Business owners nowadays are savvy and price-conscious, and our goal is to deliver above and beyond expectations.

Omniterm, being your true partner in POS, is introducing the new, compact, yet powerful 1.8 Intel Celeron Dual Core processor MINI KIOSK.

The OMNI MINI KIOSK is a fan-less, POS terminal with a scratch-proof projected capacitive touch screen. Housed in a beautiful body, the kiosk has the system performance and reliability that Omniterm products have become known for. Staying true to Omniterm tradition, The OMNI MINI KIOSK combined with the Kiosk Retrieval software, will help speed the line of customers waiting to see a movie!

Fan-less Touch Terminal



OMNI MINI KIOSK Features

- Projective Capacitive Touch Screen / Bezel Free
- Intel Celeron Dual Core 1.8GHz Processor
- Minimum - 160 GB Hard Drive
- Memory – Minimum 2GB
- Integrated 3" Thermal Roll Printer
- Integrated Card Reader
- Integrated Power Supply
- Small footprint – 10.5" wide by 12" deep
- Integrated 2D Barcode Scanner
- Low Power consumption
- VIVID LED Backlight for Reliability and Energy Savings

OMNI MINI KIOSK TERMINAL

Touch Terminal Specifications

Processor:	Intel Celeron 1037U 1.8GHz Fanless
Cores / Threads:	Dual Core / 2 Threads
Cache Memory:	2MB
Bus Speed:	5 GT/s (Giga Transfers per Second)
Display LCD:	True Flat 15" LCD with LED Backlighting
Resolution:	1024 x 768
Brightness:	Adjustable Up to 350 cd/m2
Integrated Speakers:	Integrated 2 Watt Speakers
Chipset (PCH):	NM70
Touch – Panel:	Projected Capacitive Touch
Reliability:	Over 100 Million Touches
MCR:	Integrated USB Interface Triple Track MCR with Optional Encryption
Hard Drive:	320GB 2.5" HDD or 128GB 2.5" Solid State Drive
RAM Memory:	2GB SODIMM DDR3 (1600MHz) Expandable To 4GB (2 Slots)
Video Memory:	Shared System Memory Up To 512MB
Compact Flash:	Optional SATA Adaptor
Serial Ports – 4 External:	COM1, COM2, COM4 = DB9 With Pin 9 0V/+5V/+12V (User Selectable by BIOS) COM3 = RJ45 Pin 1 +5V/+12V (Selectable by Jumper)
2 Internal:	COM5 = Primary Touchscreen COM6 = Customer Display Port (VFD)
Parallel Port:	One DB-25F
USB Ports:	6 V2.0 (2 Left Side of screen / 4 Bottom)
Cash Drawer Port:	RJ11, 12V or 24V Selectable By Jumper (Maximum 2 Drawers – Supports Open/Close)
Keyboard / Mouse Port:	Not Applicable (Use USB)
LAN Port:	RJ45 10/100/1000 Base-T (Giga LAN) RealTek RTL8111E
VGA Port:	One DB15F Display Port For Second LCD (Resolution Up to 2048 x 1536)
Audio Port:	One Line-In / One Line-Out
Mic Port:	One Mic-In
Power Supply – Terminal:	75W, 12V/6.25A 100-240V 50-60Hz Integrated Power Adaptor
Printer:	60W, 24V/2.5A 100-240V 50-60Hz Integrated Power Adaptor
Current / Power Usage:	0.28A / 31W (110V Idle Environment)
Operating Temperature:	32° F to 104° F (0° C to 40° C)
Compatible O/S:	POSReady 2009 / POSReady 7 / Windows Pro 7 / Windows Pro 8 / Windows 8 Industry Pro / Windows 10 Retail / Windows 10 Pro
Footprint:	10-1/2"W x 12"D
Dimensions:	14"W x 16-7/16"H x 12-3/16"D
Shipping Weight:	30 lbs. (Including Standard Printer and Card Reader)
Safety and EMI:	FCC / CE / RoHS